INTERIOR YELLOW ZINC COATED

INTERIOR MULTI-PURPOSE WOOD SCREW



Star Drive



Bugle Head

- Gold Zinc Coating
- Star Drive
- Type 17 Point



TER 1911-01

Scan for Tech Data





Use the proper size, grade and type of Big Timber Stainless Steel Fasteners in areas within one mile of saltwater, near swimming pools, exposure to corrosive chemicals, or other areas where corrosion is more likely to occur, such as livestock confinement, Big Timber Stainless Steel Fasteners should be considered if available, Stainless available as STX.



BENEFITS & FEATURES:

- Heat-treated hardened steel for high tensile strength and high shear strength
- Gold Zinc Coating for Interior wood construction use
- Deep Six-Lobe Star Drive Recess reduces cam-out end load
- Handles 2X the torque as Phillips or Square Drive while extending the life of the bit
- Under-head cutting nibs to aid in self countersinking
- Aggressive knurl enlarges hole to reduce splitting and drag to help draw lumber together
- V-Cut notches on threads to cut fibers for easier insertion at lower torque
- Type-17 tip for faster precise starts which eliminate "walking"
 Provides easier insertion without pre-drilling
- · Aggressive thread for great withdrawal strength
- Structural Wood Screw Backed by certified independent testing (TER 1911-01)
- International Building Code and International Residential Code Compliant

COMMON USES INCLUDE:

- Log Construction
- Timber Frames
- Laminated Beams
- Girders
- Ledger Boards
- Stair Rails
- SIP Panels
- Pole Barns

NOTE: Always follow lumber manufacturer's recommendations.

Available Sizes • #8 x 1" to #10 x 6"

AVAILABLE DRIVE AND SHANK SIZES FOR ANY INTERIOR WOOD CONSTRUCTION JOB:

T20 (#8 / 0.119 IN)

T25 (#9 / 0.135 IN)

T25 (#10 / 0.151 IN)

DIAMETER / DRIVE	LENGTH	AVERAGE ULTIMATE LOAD
0.119" / T20	1-2½"	640 lbf (Shear 515 lbf)
0.135"/ T25	2-3%"	820 lbf (Shear 595 lbf)
0.151"/ T25	1½-6"	960 lbf (Shear 710 lbf)

